



CENTURY INDUSTRIES CORPORATION

A Century Group Company

5331 STATE ROUTE 7 NEW WATERFORD, OH 44445 800-955-8443

PRODUCT SPECIFICATION SHEET



PRODUCT NAME

CENTURY ULTRA SEAL™ PROFESSIONAL DRYWALL FINISHER

ITEM CODE

332-05 (4.5 Gallon) 332-01 (1 Gallon)

UPC CODE

017581 33205 017581 33201

V.O.S./V.O.C.

Maximum V.O.S./V.O.C. is 1.7 lbs. per gallon.

FORMULATION

Dolomitic Limestone/Crystalline Silica

DESCRIPTION

Up to 25% lighter than ordinary compounds, this ready-mixed, lightweight compound is specially formulated to provide excellent adhesion. It bonds with less shrinkage and greater crack resistance than ordinary compounds for superior quality results. Easy to apply, extra white formulation for embedding any standard joint tape and for filling and finishing coats in interior gypsum panel applications. Also for covering corner bead, fasteners, trim and for skim coating entire gypsum panel surfaces. May be used for simple textures prior to painting.

DIRECTIONS

NAIL HEADS: Spot fill with a first coat of compound and as each successive finish coat is applied. All nails should be dimpled just below the surface of drywall. Allow a minimum of 24 to 48 hours to dry between applications. **TAPING--- 1ST STEP:** Beginning with a 4" broad knife, apply compound evenly and fully into wallboard joint, filling the channel formed by the wallboard edges. **TAPING--- 2ND STEP:** Center the tape over joint and press tape firmly into compound using a 4" broad knife. Tape the full length of the joint. Remove excess compound. Always feather edges and allow at least 24 to 48 hours to dry. **INSIDE CORNERS:** Cut the tape the exact length of the corner and crease it down the center before embedding it into the compound. Apply finish coats 1 side at a time allowing each side to dry a minimum of 24 hours. **OUTSIDE CORNERS:** Position metal cornerbead over exact length of corner and nail into place. Apply enough compound to cover metal band and feather edges approximately 4" from the corner. Allow a minimum of 24 to 48 hours to dry. **FINISH COAT:** Apply a final coat of compound using an 8" to 10" broad knife, feathering edges approximately 6" to 8" on each side of the taped joint or cornerbead. One finish coat should be sufficient; however, if a second coat is desired, allow 24 to 48 hours to dry before applying. **TOUCH-UPS:** Minor surface imperfections may be corrected by applying a second thin coat using an 8" to 10" broad knife, feathering edges approximately 8" to 10" on each side of the taped joint. Allow to dry a minimum of 24 to 48 hours. **FINISHING:** After the final coat is thoroughly dry the compound should be lightly sanded with a fine (200 grit) paper, being careful not to expose tape or roughen paper of exposed wallboard. Wet sanding with a damp sponge is recommended whenever practical. **ADDITIONAL TIPS:** Always stir product thoroughly before and during application. Always allow each coat to dry thoroughly before applying additional compound. After application, protect surface with an overcoat of quality drywall primer for maximum durability and protection. **THINNING:** Joint compound may be thinned by adding clean water sparingly in half pint increments. Remix completely after each addition. Over-thinning may result in excessive shrinkage, edge cracking, poor bond, and generally poor working characteristics. **IMPORTANT:** Do not mix with any other dry or ready mixed material. If material becomes frozen, let thaw naturally. Remix before use to a smooth, even consistency. **CAUTION:** Sanding dust may cause eye, nose, throat or upper respiratory irritation. Prolonged and continued exposure to a high concentration of airborne dust may result in delayed lung injury. If dry sanding, wear a NIOSH/MSHA approved respirator for protection from dust. Do not take internally. If ingested, induce vomiting. Call physician at once. The use of safety glasses is recommended. Eye contact: Remove contact lenses. Rinse eyes with water for 10-15 minutes, including under eye-lids. If irritation continues, contact physician at once.

COVERAGE

700 sq. ft. per 60 lbs.

CLEAN UP

Wash hands and tools with soap and water.

PACKAGING

Five gallon and one gallon plastic pails.