



CENTURY INDUSTRIES CORPORATION

A Century Group Company

5331 STATE ROUTE 7 NEW WATERFORD, OH 44445 800-955-8443

PRODUCT SPECIFICATION SHEET



PRODUCT NAME

SOUTHWEST TEXTURES TEXTURE PAINT

ITEM CODE

400-02 (2 Gallon) MESA SMOOTH	401-02 (2 Gallon) DESERT SAND
402-02 (2 Gallon) AZTEC MEDIUM	403-02 (2 Gallon) ROUGH ADOBE

UPC CODE

017581 40002 (Mesa Smooth)	017581 40102 (Desert Sand)
017581 40202 (Aztec Medium)	017581 40302 (Rough Adobe)

V.O.S./V.O.C.

Do not thin!

FORMULATION

Dolomitic Limestone/Crystalline Silica

DESCRIPTION

A ready-mixed, easy to use alternative wall and ceiling treatment that provides a variety of custom finishes over most interior surfaces. Southwest Decorative Texture is excellent for filling hairline cracks, pores and other surface defects. Decorative designs, including swirl, stipple, roller and brush effects, can be created easily.

DIRECTIONS

SURFACE PREPARATION: Small cracks or rough surfaces can easily be textured over without time-consuming patch work. Surface must be sound, clean and dry. Use a stiff bristle brush to remove dirt, dust, loose plaster and paint. Remove any gloss from surface to be coated by sanding. New wallboard, water-stained areas, and patches should all be sealed with a quality primer/sealer prior to texture application. **NOTE:** Wallpaper and adhesive must be removed prior to application. Failure to do so may result in loss of adhesion, paper separation from wall, or bleeding-through of old wallpaper paste or glue.

MATERIAL PREPARATION: Mix thoroughly before using, stirring with a lifting motion. If a thinner consistency is desired, add clean water in small amounts not to exceed 8 oz.-12 oz. per container. **DO NOT OVERTHIN PRODUCT!** Overthinning may result in excessive shrinkage, edge cracking, reduced bond, and generally poor working characteristics.

APPLICATION CONDITIONS

May be applied with a medium nap or looped texture roller, trowel or texture brush. Apply a thick coat to small areas (approximately 4' by 4'), making sure to thoroughly and evenly cover the working surface. After the initial area is coated, immediately apply a second coat and finish to desired texture. Make sure to work in sections no larger than 4' by 4' so that you can easily smooth out unwanted patterns and to ensure that adjoining areas are blended before material sets up. **ROOM TEMPERATURE:** Should be above 50° F (10° C) during application and drying time.

HELPFUL HINTS: Practice on a sample surface until you are satisfied with texture appearance. Almost anything can be used to create attractive, unique and professional textures-- just use your imagination! **NOTE:** Southwest Decorative Texture is not warranted washable. For durability and washability, apply a quality interior latex or oil base paint as a final decorative coat. For interior use only!

COVERAGE

Approximately 40-60 square feet per gallon depending on texture desired, surface being covered and method of application. Porous surfaces will require more material to cover than will non-porous surfaces.

CLEAN UP PACKAGING

Wash hands and tools with soap and water.

2-gallon plastic pails.