



# CENTURY INDUSTRIES CORPORATION

A Century Group Company

5331 STATE ROUTE 7 NEW WATERFORD, OH 44445 800-955-8443

## PRODUCT SPECIFICATION SHEET



### PRODUCT NAME

CENTURY ALL PURPOSE TOPPING COMPOUND

### ITEM CODE #

340-05 (5 Gallon)

### UPC CODE #

017581 34005

### V.O.S./V.O.C.

Do not thin! Maximum V.O.S./V.O.C. is 1.7 lbs per gallon.

### FORMULATION

Dolomitic Limestone/Crystalline Silica

### DESCRIPTION

Century All Purpose Topping Compound is specially formulated to give superior finishing results when used over Century All Purpose Joint Compound and powder taping compounds. It is recommended for the finishing coats over fastener heads, corner beads, trim and previously taped drywall joints. Can also be used for applying simple textures or skim coating, prior to painting. Important: Do not use Century All Purpose Topping Compound for taping or laminating. Do not mix with any other materials, including other premixed or dry powder joint compounds. Store in a warm area (50°F minimum) for at least 24 hours before using product. Protect from freezing. If this product does freeze, allow to thaw naturally in a warm place, then remix before applying. Do not force thaw. NOTE: Mix thoroughly before using or thinning.

### DIRECTIONS

After the initial compound is thoroughly dry apply a thin coat of compound feathering edges approximately 6" to 8" on each side of the taped joint. Always allow 24 hours to dry between applications. After the first finish coat has thoroughly dried apply a second thin coat using a 10" broad knife feathering edges approximately 8" to 10" on each side of the taped joint. Allow to dry a minimum of 24 hours. FINISHING: After the final coat is thoroughly dry the compound should be lightly sanded with a fine (200 grit) paper, being careful not to expose tape or roughen paper of exposed wallboard.

### APPLICATION CONDITIONS

In cold weather, provide sufficient heat and ventilation so that compound will dry thoroughly in 24 to 48 hours. Maintain heat at not less than 50°F (10°C) during application and until completely dry. For painting and decorating follow that manufacturer's directions. ADDITIONAL TIPS: Always stir product thoroughly before and during application. Wet sanding or sponging is recommended whenever practical. After application, protect surface with Ultra Seal Primer/Sealer for maximum durability. STORAGE: Keep container sealed. Store in dry location at room temperatures. Protect contents from freezing, and avoid exposure to extreme heat and direct sunlight. NOTE: This product is manufactured to meet ASTM Specification C 475-94.

### COVERAGE

700 sq. ft. per 60 lbs.

### CLEAN UP

Wash hands and tools with soap and water.

### PACKAGING

5-gallon plastic pails