



**CENTURY  
INDUSTRIES**  
A Division of Century Container, LLC

## TECHNICAL DATA SHEET



## Pro-Q® 8-Year Ultra Premium Driveway Filler & Sealer

Item #10-492-05

- 8-Year Protection
- High Solids Formula for Good Filling & Long Term Protection
- Fast & Easy to Apply
- Dries Black

### Manufacturer

Century Industries  
5331 State Route 7  
New Waterford, Ohio 44445  
Phone: 800-955-8443  
Fax: 330-457-7228  
www.centuryindustriescorporation.com

### Description

A polymer modified asphalt emulsion based driveway resurfacer designed to beautify, protect and renew asphalt pavement surfaces. Fortified with sand for added strength, filling, slip resistance and durability.

### Uses

- All types of asphalt pavements.
- DO NOT USE on concrete or masonry surfaces.
- All asphalt pavement must weather at least six (6) months, including one summer, before using this product.

### Surface Preparation

- All cracks and holes should be repaired with Century Rubberize™ Heavy Duty Crack Filler or Century Latex Plus Driveway Patch. Allow repaired areas to cure as directed before sealing.
- For best results, surface must be thoroughly cleaned. Remove all loose dirt and foreign material and scrub all grease and oil spots with a detergent to prevent subsequent peeling and flaking. Flush entire pavement clean with water, being sure to not leave standing water.

### Application

Century Pro-Q® Ultra Premium Driveway Filler & Sealer is packaged ready to use. No stirring is necessary. With pavement still damp, apply a uniform coat of sealer, being sure to avoid heavy or uneven application which may result in cracking or tracking. A second coat should be applied after the first coat has dried "to the touch" or within 24 hours at stated

coverage rate. A rubber squeegee or brush is recommended for application.

### Drying Time

Allow Century Pro-Q® Ultra Premium Driveway Filler & Sealer to dry to the touch, approximately 3 to 6 hours, depending on weather conditions. Allow product to cure at least 8 to 24 hours under ideal conditions (70° F and less than 50% humidity), testing for trafficability before opening area to regular use.

### Clean Up

While wet, use soap and water.

### Weather Conditions

Do not apply when temperature is expected to drop below 60° F or when rain is possible within the next 48 hours.

### Coverage (Approximate)

Depending on pavement porosity, coverage will vary from 250 to 350 sq. ft. per 4.75 gallon pail.

### Precautions

- Do Not Thin
- Do Not Store Container At Temperatures Below 40° F
- Do Not Freeze
- Do Not Allow Traffic Until Fully Cured

### Safety and Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content is 50 Gm/Liter Max
- KEEP OUT OF REACH OF CHILDREN

**CALIFORNIA PROPOSITION 65 CHEMICAL WARNING:**

This product contains chemicals known to the state of California to cause cancer.

**Packaging**

Item #	Container Size	Pack	Weight
10-492-05	4.75 Gallon	1	57.5 lbs.

\* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Petroleum Asphalt	8052-42-4
Hydrous Aluminum Silicate	1332-58-7
Silicon Dioxide	14808-60-7
Water	7732-18-5
Blend of Fatty Amines	Proprietary
Polymer	Proprietary